

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : <b>A61B 19/04, A61F 6/04</b>		A1	(11) International Publication Number: <b>WO 94/02080</b> (43) International Publication Date: <b>3 February 1994 (03.02.94)</b>
<p>(21) International Application Number: <b>PCT/GB93/01397</b> (22) International Filing Date: <b>5 July 1993 (05.07.93)</b></p> <p>(30) Priority data: <b>9215117.4 16 July 1992 (16.07.92) GB</b></p> <p>(71) Applicant (<i>for all designated States except US</i>): <b>ISIS INNOVATION LIMITED [GB/GB]; 2 South Parks Road, Oxford OX1 3UB (GB).</b></p> <p>(72) Inventor; and (75) Inventor/Applicant (<i>for US only</i>) : <b>BULSTRODE, Christopher, John, Kent [GB/GB]; Wits End, Old Road, Wheatley, Oxfordshire OX3 3INX (GB).</b></p> <p>(74) Agent: <b>PENNANT, Pyers; Stevens, Hewlett &amp; Perkins, 1 Serjeants' Inn, Fleet Street, London EC4Y 1LL (GB).</b></p>		<p>(81) Designated States: <b>JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b></p> <p><b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	
<p><b>(54) Title:</b> PROTECTIVE ARTICLES</p> <p><b>(57) Abstract</b></p> <p>A protective article, e.g. a surgeon's glove, comprises inner and outer layers of transparent or translucent polymeric material. Between the layers is sandwiched a solid particulate water-soluble dye. On rupture of the glove, liquid enters the cavity between the layers and dissolves the dye. This causes a colour change which warns the user that the glove has been ruptured.</p>			

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	L1	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

PROTECTIVE ARTICLES

5       The present invention is concerned with protective articles, of the kind which are designed to indicate if a breach of their protective integrity has occurred. One example of a protective article according to the invention is a surgeon's glove.

10      It is estimated that some 25% of surgeons gloves are perforated by the end of an operation. In order to reduce the chance and severity of such perforations surgeons typically wear two pairs of gloves. The current problems with Hepatitis and AIDS 15 have made surgeons and others involved in treating such patients even more aware than before of the potential risk of being contaminated by patients blood or other body fluids.

Clinica, No. 337, p24, 1989 describes a double 20 layered glove with a dark coloured inner layer and a lighter coloured outer layer, the two being held in close contact by a vacuum such that the colour of the darker inner layer is predominant. If perforated the layers separate and the colour of the outer layer 25 becomes more prominent. An alternative colour change system is suggested of providing a water or oxygen sensitive chemical indicator between the layers but no details are given. The gloves have not achieved commercial success.

30      There is a need for protective articles, in particular surgeon's gloves, and gloves for other medical purposes including examination, which will warn the user immediately by highly visible colour change that perforation of the protective article has occurred 35 and that he should immediately consider replacement.

This invention provides a protective article

- 2 -

comprising an inner layer and an overlying outer layer, the outer layer being translucent or transparent and both layers being of polymeric material and impermeable to fluid, the two layers being sealed together so as to

5 define between them a closed cavity within which is dispersed a powdered soluble dye which, on perforation of either layer and entry of fluid into the cavity, dissolves in the fluid in the cavity to exhibit a colour change visible through the outer layer.

10 The protective article comprises an inner layer and an overlying outer layer. Both layers are impermeable to the fluid, generally aqueous fluid such as water or body fluids with which the article is likely to come into contact. Both layers are of the  
15 same or different polymeric material. Either or both layers may be rigid, but more usually both layers are flexible sheets of rubber or a plastics material. Particularly for surgeon's gloves, latex rubber is the preferred material. The outer layer needs to be  
20 translucent or transparent, to the extent that the colour change, resulting from perforation of either layer, is visible through it.

The two layers are sealed together, so as to define a closed cavity between them. It is generally  
25 convenient for one layer to be sealed to the other layer along a continuous line extending round its periphery. That continuous line then forms a ring within which is defined a closed cavity between the two layers.

30 Within this cavity is dispersed a powdered soluble dye. The particles of dye are of a sufficiently small size and dispersed sufficiently widely that they are substantially invisible through the outer layer and do not substantially colour the  
35 article. The particle size of the powdered dye may be as small as conveniently possible. The dye may be

present in admixture with a colourless extender. The dye needs to be soluble in fluid, for example aqueous fluid such as body fluids, with which the article is expected to come in contact.

5        If either layer is perforated, then it becomes possible for fluid to enter the cavity between them. The fluid may tend to spread by capillary action within the cavity, because the outer layer overlies the inner layer. The dye dissolves in the fluid, and the  
10      colour of the dye is imparted to the fluid and becomes visible through at least the outer layer of the article.

Preferred dyes are highly water soluble and of dark colour, i.e. having a high colour density, such  
15      as black or blue, since this produces a more dramatic colour change against the normal colour of rubber or plastic sheets. However, any water soluble dye which can be provided in powder form can be used. The colour should be chosen to give a large change in  
20      colour tone from that of the colour of the outer layer (or seen through the outer layer) of the article itself. Preferred dyes include diazol brilliant blue GL GMS50 and diazol fast black JRA 2UAD, both supplied by ICI.

25       The powdered dye may be dispersed throughout the cavity or in specific regions within the cavity. The density of the particle dispersion, and the size of the dye particles, should be chosen such that there is a marked and easily visible colour change when fluid  
30      enters the cavity.

Preferably the particle dispersion is present at a density of 0.1 - 10.0 g/m<sup>2</sup>, particularly 0.2 - 2.0 g/m<sup>2</sup>. At densities outside this range the colour change, on perforation of either layer and  
35      solution of the dye in incoming fluid, may be too slight to be easily observed.

Preferably the dispersed particles have an average size in the range of 1 - 100 µm. Larger particles may be satisfactory if they can be uniformly dispersed in the cavity and if they dissolve

5 sufficiently rapidly in incoming fluid to generate the desired colour change.

Bags, for example laboratory sample bags

constitute one example of protective articles according to this invention. Some laboratory practices require

10 the double bagging of many substances. There is a need for a purpose-made bag which would rapidly indicate any perforation or leakage. Double walled bags are formed with one layer inside the other, the two layers being sealed together around the neck of the bag, and a  
15 powdered soluble dye being dispersed in the resulting cavity between the two layers.

Another example of protective articles according to the invention are condoms, which may be constructed along the same lines as gloves (see below).

20 Although the examples specifically mentioned herein may be regarded as containers, the invention is not limited to articles which are containers. Tamper-proof seals or other flat sheet formats are readily made according to the invention.

25 A preferred example of protective articles according to the invention is, as mentioned above, gloves particularly examination gloves and surgeon's gloves. Surgeon's gloves are currently made with one or two layers of PVC film or more usually latex rubber,  
30 of which at least the outer layer is translucent or transparent. Total film thickness is usually of the order of 0.05 mm to 0.5 mm. Gloves according to this invention may conveniently be formed by hermetically sealing the inner layer and the outer layer around the  
35 wrist, with the powdered dye contained in the cavity so formed. Alternatively, the glove may be constructed

- 5 -

such that a number of cavities are formed between the two layers, all or only some of which contain the dye.

As a further alternative, the glove may be constructed such that the double layer is applied only to more

5 vulnerable areas, for example the thumb and forefinger, the remainder of the glove being of single layer construction.

Example 1

10 Two identical surgeon's gloves were produced by a standard natural rubber latex dipping process. The thickness of each glove was 0.12 to 0.15 mm. One glove was placed on a former identical to the one on which it had been made, taking care to prevent air entrapment. Any powder on the outside surface was removed by washing with isopropanol. The dye was applied as a fine powder in a 1:1 mixture with an inert colourless material such as corn starch or sodium chloride. A latex adhesive was applied to a ring about 20 2 cm around the cuff and the four crotch regions. This was dried for a few minutes at 70°C. The second glove was pulled on to the former-supported glove taking care to exclude visible air bubbles. The two gloves were sealed by applying hand pressure to the adhesive 25 treated regions. The complete glove was stripped from the former.

Powdered materials adhere readily to latex rubber surfaces. In surgeon's gloves according to this invention, it is advantageous to have quite a lot of 30 powdered material between the two layers, to provide a measure of lubrication. If the dye were used as the sole powdered material for this purpose, the glove would be too dark in its initial state for any very obvious colour change to be visible after perforation 35 and ingress of fluid. It is therefore convenient to mix the dye with an extender. As received, the dyes

- 6 -

were coarsely particulate materials. They were therefore mixed with corn starch and the mixture ground to a finer particle size. The weight ratio of dye:corn starch used was 1:1, but this can readily be varied so  
5 as to provide a desired colour intensity of the glove, both before and after perforation. If the powdered mixture is simply poured over the inner latex rubber layer on the former, enough sticks to the rubber surface to provide the desired lubricating and colour-  
10 change effects.

It may be advantageous to assemble the glove finger tips down, so that any loose powder tracks to the finger tips which are the most likely site for perforation.

15 A pair of gloves was made as described above using the diazol brilliant blue GL GMS50 dye. A fairly high density of dye was used, and the gloves looked slightly darker than ordinary surgeon's gloves before they became covered in body fluids. Once covered in  
20 body fluids, they were virtually indistinguishable from ordinary gloves. As soon as a perforation was created at a finger tip, a good colour change occurred which was easily visible even with the gloves still covered in body fluids.

25 Another pair of gloves was made using diazol fast black JRA 2UAD dye. The dye was used at a lower density such that even in the air the gloves were indistinguishable from unpigmented double gloves. When immersed in body fluids and perforated, a colour change  
30 occurred which was, however, less obviously noticeable than was the case with the earlier pair.

- 7 -

Example 2

Process for making the IND-X Glove

Materials Required

Beadless surgical glove with palm thickness  
5 0.14-0.15 mm approx. (inner layer).  
Beadless surgical gloves with palm thickness  
0.17 - 0.18 mm approx. (outer layer).  
Diazol brilliant blue dye.  
Dry alcohol e.g. dried industrial methylated  
10 spirit.  
A latex contact adhesive.  
Cotton wool sticks or the like.

Equipment Required

15 Former identical to one used to make the  
gloves above.  
High speed grinding mill e.g. Silverson.  
Oven at 70°C.  
Brushes.  
20 Stirred vessel.

Preliminaries

1. Both gloves must be of same size and must be  
well leached, fully dried and coated with bioabsorbable  
25 corn starch or other surface coating.  
2. The dye is suspended in the dry alcohol at a  
concentration of about 5% using a Silverson stirrer.  
This has the effect of reducing the particle size of  
the dye as well as dispersing it. The particles in the  
30 dispersion range from 1 - 120 µm in size, with the  
majority in the range 10 - 20 µm.

Procedure

1) Pull the thin glove onto the former until all  
35 finger tips are in contact with the former and no  
creases remain in glove.

- 8 -

- 2) Support former over a collecting vessel with fingers pointing downwards.
- 3) Apply suspension dye, which is being continuously stirred, to the glove with a brush. Allow 5 the excess to drain downwards. This has the effect of removing some of the powder coating as well.
- 4) Dry in air to leave a coating of dye all over the glove except for about a 5 cm ring around cuff. A typical glove has about 0.03 g of particulate dye, 10 corresponding to a density of about 0.7 g/m<sup>2</sup>.
- 5) Using cotton wool sticks soaked in alcohol, remove all powder (dye and corn starch) for finger tips, crotch between fingers and 5 cm band near cuff.
- 6) Apply the latex adhesive to the areas 15 mentioned in 5).
- 7) Dry adhesive completely at 70°C (about 5-10 mins).
- 8) Pull the second glove onto the first with cuff folded over.
- 20 9) Press down finger tips and crotches to complete bonding and exclude as much air as possible from between the layers.
- 10) Roll down the cuff of the outer glove over the inner and press to complete bonding.
- 25 11) Strip the completed IND-X glove from the former and evert the glove.

37 pairs of the gloves so made have been subjected to clinical trials by six surgeons in various hospitals. Reaction has been very favourable. The 30 gloves are reported as comfortable, sensitive and robust in use. When perforation of either layer does take place, the resulting blue discolouration is easily seen, even when little body fluids are present.

CLAIMS

5

1. A protective article comprising an inner layer and an overlying outer layer, the outer layer being translucent or transparent and both layers being of polymeric material and impermeable to fluid, the two layers being sealed together so as to define between them a closed cavity within which is dispersed a powdered soluble dye which, on perforation of either layer and entry of fluid into the cavity, dissolves in the fluid in the cavity to exhibit a colour change visible through the outer layer.
10. Protective article as claimed in claim 1, wherein both layers are flexible films of rubber or plastics material.
15. Protective article as claimed in claim 1 or claim 2, wherein both layers are of latex rubber.
20. Protective article as claimed in any one of claims 1 to 3, wherein the dye is soluble in water and body fluids to exhibit the desired colour change.
25. Protective article as claimed in any one of claims 1 to 4, wherein the powdered dye is present in admixture with a colourless carrier.
30. Protective article as claimed in any one of claims 1 to 5, wherein the article is a glove.
35. Protective article as claimed in claim 6, wherein the glove is a surgeon's glove.
40. Protective article as claimed in any one of claims 1 to 5, wherein the article is a bag.
45. Protective article as claimed in any one of claims 1 to 5, wherein the article is a condom.
50. 10. Protective article as claimed in any one of claims 1 to 9, which is supplied in sterile form.

**INTERNATIONAL SEARCH REPORT**

Inten	nal Application No
PCT/GB 93/01397	

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC 5 A61B19/04 A61F6/04

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 A61B A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 368 456 (RICHARDSON) 16 May 1990	1-4,6,7, 10
Y	see claims 1,5 ---	8
X	WO,A,89 05449 (CUKIER) 15 June 1989 see page 12, paragraph 1 ---	1,2,4-7, 9,10
X	EP,A,0 411 732 (KECK) 6 February 1991 see column 3, paragraph 2 -paragraph 3 ---	1,5,9
Y	DATABASE WPI Section Ch, Week 9135, Derwent Publications Ltd., London, GB; Class B07, AN 91-256049 & JP,A,3 165 770 (NIPPON MED SUPPLY K) 17 July 1991 see abstract ---	8
		-/-

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*B\* earlier document but published on or after the international filing date
- \*I\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

16 November 1993

22.11.93

Name and mailing address of the ISA

European Patent Office, P.O. 5818 Patenlaan 2  
NL - 2280 HU Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl  
Fax: (+ 31-70) 340-3016

Authorized officer

BARTON, S

**INTERNATIONAL SEARCH REPORT**

International application No. PCT/GB 93/01397	
--	--

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB,A,2 218 617 (SMITH AND NEPHEW) 22 November 1989 see page 19, paragraph 1 ---	5
A	EP,A,0 430 400 (ULBRICH) 5 June 1991 see column 6, line 9 ---	10
A	US,A,3 633 216 (SCHONHOLTZ) 11 January 1972 see column 2, line 37 - line 52 -----	1

2

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

PCT/GB 93/01397

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP-A-0368456	16-05-90	AU-B-	625820	16-07-92
		AU-A-	4323089	18-04-90
		WO-A-	9003632	05-04-90
		GB-A-	2242817	16-10-91
		JP-T-	5503585	10-06-93
		US-A-	5224221	06-07-93
-----				
WO-A-8905449	15-06-89	US-A-	4843014	27-06-89
		AU-A-	2797789	05-07-89
		EP-A-	0403483	27-12-90
		JP-T-	3501504	04-04-91
		US-A-	4910803	27-03-90
-----				
EP-A-0411732	06-02-91	DE-C-	3925938	12-04-90
-----				
GB-A-2218617	22-11-89	AU-B-	605419	10-01-91
		AU-A-	3327389	26-10-89
		EP-A-	0350147	10-01-90
		JP-A-	1320052	26-12-89
		US-A-	5180605	19-01-93
-----				
EP-A-0430400	05-06-91	US-A-	4951815	28-08-90
-----				
US-A-3633216	11-01-72	DE-A-	2158409	22-06-72
		FR-A-	2117119	21-07-72
		GB-A-	1337617	14-11-73
-----				